

PR-WS15W-IP

IP ONVIF 15W Indoor wall speaker

Compact and efficient, this 15W indoor IP horn speaker delivers crystal-clear audio with a powerful sound output of 101dB, ensuring announcements and alerts are heard with clarity. Ideal for indoor spaces, it combines high-performance audio with easy installation.









MAIN FEATURES

• PR-WS15W-IP IP ONVIF 15W Indoor wall speaker

• Amplifier: Built-in 15W Amplifier

• Max SPL: 101dB

• Frequency Response: 80Hz~20KHz

• Installation: Wall Mount

• Power: DC12V / PoE~1.25Amp

• Power Consumption: 15W Max

• Operation Temperature: -30-60°C

• Protection Rate: IP55

• Dimensions: 296*196*157mm (W x H x D)

• Net Weight: ~3Kg

• Power supply not included



https://provision-isr.com



SPECIFICATIONS

| Speaker | |
|-----------------------|--|
| Max SPL | 101dB |
| Frequency Response | 80Hz~20KHz |
| Audio | |
| Usage | Real-Time Audio Broadcast / Up to 10 pre-loaded files (Triggered by API) |
| Codec | OPUS 48kHz, MP3 44.1kHz, G.722 ADPCM 16kHz, G.711 PCMU 8kHz, G.711 PCMA 8kHz |
| Amplifier | |
| Amplifier | Built-in 15W Amplifier |
| Network | |
| Protocols | SIP, ONVIF, HTTP, HTTPS, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NTP, Multicast |
| VoIP | 2 SIP Accounts SIP Direct IP Call RTP Multicast |
| Security | Password protection, IP address filtering, Digest authentication, User access log |
| Onvif | Profile S |
| Interface | 10/100 Base-TX, RJ45 |
| GENERAL | |
| Power | DC12V / PoE~1.25Amp |
| Power Consumption | 15W Max |
| Protection Rate | IP55 |
| Installation | Wall Mount |
| Dimensions | 296*196*157mm (W x H x D) |
| Net Weight | ~3Kg |
| Operation Temperature | -30-60°C |